

W H Y T E
P E R F O R M A N C E B Y D E S I G N



2015 UK DEALER BOOK



G-150 S

TYPICAL USAGE: GRAVITY ENDURO/TRAIL

SRP £2,799



Colour	Matt Granite/Aqua & Lime
Sizes Available	S, M, L
Weight	13.5Kg
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and InterGrip seat clamp, alloy symmetrical SCS rear Triangle
Fork	RockShox Pike 27.5", RC, 150mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub 12mm X 142mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes
Rims	WTB Frequency Race i23 Rims with TCS System, I-Beam technology, Tubeless Ready
Tyre	WTB Vigilante AM TCS Light Fast Rolling 27.5 X 2.3" Folding Front, WTB Trail Boss TCS Tough Fast Rolling 27.5" X 2.25" Folding Rear
Shift Levers	SRAM X-1, MMX Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X-1, 11 Speed Alloy
Cassette	SRAM XG-1180 10-42, 11 Speed
Chain	SRAM PCX1, 11 Speed
Crankset	SRAM X1-1200 GXP, 32T, 11 Speed Alloy
Bottom Bracket	SRAM GXP Team 73mm
Seatpost	RockShox Reverb 125 Stealth, MMX MatchMaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 750mm Wide
Stem	Whyte Gravity Stem, 50mm
Grips	Whyte Lock-on
Front Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing
Rear Brakes	SRAM Guide R, 4 Pots, 170mm Rotor, Internal Routing
Brake Levers	SRAM Guide R, MMX Matchmaker

With its new single ring specific SCR frame, and a full-compliment of race ready components, the G-150 S is better - and faster - than ever.

The 2015 frame increases torsional stiffness and provides internal brake routing, Whyte's all new "InterGrip" integrated seat post clamping system and a SCS Rear Triangle which is 1 by 11 specific.

This bike is ready for anything you want to throw at it from hardcore trail riding to Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16-19mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74.7	594	343	808
M	66.5	74.5	608	343	816
L	66.5	74.3	628	343	823
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1154	425	30.9	95	406
M	1169	425	30.9	110	445
L	1189	425	30.9	120	483

G-150 WORKS

TYPICAL USAGE: GRAVITY ENDURO/TRAIL

SRP £3,999



Colour	Matt Burnt Orange/Black
Sizes Available	S, M, L
Weight	13.2Kg
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and InterGrip seat clamp, alloy symmetrical SCS rear Triangle
Fork	RockShox Pike 27.5", RCT3, 150mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle
Rear Shock	RockShox Monarch Plus Debonair, RC3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
Rear Hub	SRAM Rail 50, 12 x 142mm
Front Hub	SRAM Rail 50, 15 x 100mm
Spokes	SRAM Rail 50, StSt Butted
Rims	SRAM Rail 50, 23mm wide 27.5", Full UST Rims
Tyre	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	SRAM X01, MMX Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X01, 11 Speed, Carbon
Cassette	SRAM XG1195 10-42, 11 Speed
Chain	SRAM PCXX1, 11 Speed
Crankset	SRAM X01 32T, 11 Speed
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	RockShox Reverb Stealth 125mm, MMX Matchmaker, 30.9 X 380mm
Seat	Fizik Gobi XM, Matt/Gloss, Mg Rails
Bar	Easton Haven 35mm Oversize, 750mm wide
Stem	Easton Haven 35mm Oversize, 50mm long
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor, Internal Routing
Rear Brakes	SRAM Guide RSC, 4 Pots, 170mm Rotor, Internal Routing
Brake Levers	SRAM Guide RSC MMX Matchmaker

This is the bike our Gravity Enduro team race on, and as such, it's got the best of everything, from SRAM, Easton, Maxxis, and of course, Whyte.

This bike is ready for anything you want to throw at it from hardcore trail riding to Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

The 2015 frame increases torsional stiffness and provides internal brake routing, Whyte's all new "InterGrip" integrated seat post clamping system and a SCS Rear Triangle which is 1 by 11 specific.

Dropout Code	DROPWHQ4SH
Shock Stroke and Sag Setting	63mm, Sag 16-19mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74.7	594	343	808
M	66.5	74.5	608	343	816
L	66.5	74.3	628	343	823
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1154	425	30.9	95	406
M	1169	425	30.9	110	445
L	1189	425	30.9	120	483

T-130 SX

TYPICAL USAGE: TRAIL

SRP £1,999



Colour	Matt Aqua/Lime
Sizes Available	XS, S, M, L
Weight	13.7Kg
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and Intergrip seat clamp, alloy rear Triangle with 12mm E-Thru 142 dropouts
Fork	SR Suntour Aion LO-R 27.5" CTS, 130mm Travel, Tapered steerer and 15QR
Rear Shock	Fox Float Performance with Boost Valve, Rebound Adjustment and CTD Adjust
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub 12mm X 142mm Through Axle, 32
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB Frequency Team i19 27.5" TCS System, I-Beam technology, Tubeless Ready, 32 Hole
Tyre	WTB Beeline, TCS, Light Fast Rolling 27.5" X 2.2" Folding Bead
Shift Levers	Shimano Deore, I-Spec, 10 Speed, Black
Front Derailleur	Shimano Deore, High Direct Mount, 10 Speed, Black
Rear Derailleur	Shimano SLX Shadow Plus, 10 Speed
Cassette	Shimano HG81 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Race Face Ride, 36-22, 10 Speed, Compact Double
Bottom Bracket	Race Face
Seatpost	X-Fusion HiLo 125mm Stealth, 30.9 X 380mm
Seat	Whyte Custom, dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 750mm Wide
Stem	Whyte Gravity Stem, 50mm XS, 60mm S, 70mm M & L
Grips	Whyte Lock-on
Front Brakes	Shimano M-615, 180mm Rotor, Internal Routing
Rear Brakes	Shimano M-615, 160mm Rotor, Internal Routing
Brake Levers	Shimano M-615, I-Spec

Our entry level 130mm travel 650b bike is available all the way down to an extra small size, so the broadest possible spread of riders can benefit from this great new platform.

Light-weight WTB Frequency Team TCS rims and TCS tyres give a Tubeless ready wheelset which when combined with the SR Aion fork and a Fox Performance rear shock give an excellent all-round package.

Internal routing keeps cables and hoses out of harms way and with our new rubberised frame grommets it's totally water tight.

Dropout Code	DROPWHQ4SH
Shock Stroke and Sag Setting	63mm, Sag 19mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Recommended Mudguards	N/A

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	67.5	74.1	549	331	761
S	67.5	73.8	574	331	763
M	67.5	73.5	594	331	766
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1087	420	30.9	100	368
S	1112	420	30.9	107	406
M	1132	420	30.9	115	445

T-130 S

TYPICAL USAGE: TRAIL
SRP £2,299



Colour	Matt Orange/Black
Sizes Available	S, M, L
Weight	13.5Kg
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and Intergrip seat clamp, alloy rear Triangle with Maxle 142 dropouts
Fork	RockShox Revelation 27.5", RL, 130mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub 12mm X 142mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB STi23 27.5" Rims with TCS System, Tubeless Ready
Tyre	WTB Trail Boss, TCS Light Fast Rolling 27.5" X 2.25", Folding Front, WTB Beeline, TCS Light Fast Rolling 27.5" X 2.2", Folding Rear
Shift Levers	SRAM X-9 MMX Matchmaker, 10 Speed
Front Derailleur	SRAM X-5, High Direct Mount, 10 Speed
Rear Derailleur	SRAM X-9, Type 2, 10 Speed
Cassette	SRAM PG-1030 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM S1400 GXP, 36-22 29er Trail Ratio, Compact Double, 10 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	RockShox Reverb 125mm Stealth, MMX Matchmaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S, 70mm M/L
Grips	Whyte Lock-on
Front Brakes	Avid DB5, 180mm Rotor, Internal Routing
Rear Brakes	Avid DB5, 160mm Rotor, Internal Routing
Brake Levers	Avid DB5 MMX Matchmaker

The new T-130 platform is incredibly playful when the trail points downhill; with a 20spd drivetrain, you'll have no trouble getting to the top of the hill feeling fresh and ready to have fun.

The T130 is designed to be a full suspension version of our award winning 900 series hardtails. 130mm travel front and rear and a long and low geometry will give you full trail control.

A low slung shock gives the T130 plenty of stand-over height and suspension kinematics that makes the bike really "pump" through your favourite singletrack.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 19mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Recommended Mudguards	N/A

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.5	73.8	574	331	763
M	67.5	73.5	594	331	766
L	67.5	73.3	609	331	776
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1112	420	30.9	107	406
M	1132	420	30.9	115	445
L	1147	420	30.9	130	483

T-130 WORKS SCR

TYPICAL USAGE: TRAIL

SRP £2,999



Colour	Matt Zinc/Apple
Sizes Available	S, M, L
Weight	13Kg
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip seat clamp, alloy symmetrical SCS rear Triangle
Fork	RockShox Pike 27.5", RC, 130mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	SRAM Roam 40, 12 x 142mm
Front Hub	SRAM Roam 40, 15 x 100mm
Spokes	SRAM Roam 40, StSt Butted
Rims	SRAM Roam 40, 21mm wide 27.5", Full UST Rims
Tyre	Maxxis Ardent TR 27.5 X 2.25" EXO Sidewall protection, Folding Front, Maxxis Ardent Race TR 27.5 X 2.2" EXO Sidewall protection, Folding Rear
Shift Levers	SRAM X-1, Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X-1, 11 Speed Alloy
Cassette	SRAM XG-1180 10-42, 11 Speed
Chain	SRAM PCX1, 11 Speed
Crankset	SRAM X1-1400 GXP, 32, 11 Speed Alloy
Bottom Bracket	SRAM GXP Team 73mm
Seatpost	RockShox Reverb 125 Stealth, MatchMaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S, 70mm M/L
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RS, 4 Pots, 180mm Rotor, Internal Routing
Rear Brakes	SRAM Guide RS, 4 Pots, 160mm Rotor, Internal Routing
Brake Levers	SRAM Guide RS, Matchmaker

The Works SCR features our new single ring specific frame with mega stiff symmetrical chainstays, a full width main pivot for extended bearing life and maximised suspension performance.

The T130 is designed to be a full suspension version of our award winning 900 series hardtails. 130mm travel front and rear and a long and low geometry will give you full trail control.

SRAM Roam 40 Wheels feature 21mm wide welded UST Tubeless rims and are combined with Maxxis TR tyres to give exceptional levels of control.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16-19mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.5	73.8	574	331	763
M	67.5	73.5	594	331	766
L	67.5	73.3	609	331	776
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1112	420	30.9	107	406
M	1132	420	30.9	115	445
L	1147	420	30.9	130	483

901

TYPICAL USAGE: TRAIL
SRP £1,199



Colour	Matt Zinc/Lime
Sizes Available	S, M, L, XL
Weight	12.2Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Get A Grip seat clamp system, Internal Stealth Reverb routing
Fork	RockShox Sektor Gold 27.5" Lock-out, Maxle Light 130mm Travel, Solo Air, Adjustable Compression and Rebound, Tapered Steerer
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 15mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	Whyte Trail 21 Offset Disc rim, 32 Hole
Tyre	Maxxis Ardent, 27.5" X 2.25" 60TPI Folding Front, Maxxis Ardent Race, 27.5" X 2.2" 60TPI Folding Rear
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed
Rear Derailleur	SRAM X-7 Type 2 Medium Cage, 10 Speed, Custom Green
Cassette	SRAM PG-1020, 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM FC S1000, GXP, 38-24, 10 Speed, Double Compact
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, Low Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S/M, 70mm L, 80mm XL
Grips	Whyte Custom Lock-on
Front Brakes	Avid DB 3, 180mm Rotor
Rear Brakes	Avid DB 3, 160mm Rotor
Brake Levers	Avid DB 3

With the 901, it's all about the geometry - it will make you feel more confident in all situations than any hardtail you've ever ridden.

The award winning 901 gains the "Get A Grip" seat post clamp system in 2015. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Awarding a magnificent 5 Stars in their MidRange MTB Megatest (Spring 2014), IPC's What Cycle Magazine describes the 901 as "an inspiring, near-faultless bike"

Dropout Code	DROPWH14
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73	599	305	777
M	66.5	73	618	305	805
L	66.5	73	635	305	832
XL	66.5	73	654	305	861
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1119	425	30.9	110	406
M	1139	425	30.9	120	455
L	1169	425	30.9	140	491
XL	1189	430	30.9	150	533

905

TYPICAL USAGE: TRAIL

SRP £1,599



Colour	Matt Orange/Black
Sizes Available	S, M, L, XL
Weight	11.8Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Get A Grip seat clamp system, Internal Stealth Reverb routing
Fork	RockShox Revelation RL, 27.5" Lock-out, Maxle Light 130mm Travel, Fast Black coating, Solo Air, Adjustable Compression and Rebound, Tapered Steerer
Headset	FSA No. 57E Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Hope EVO II with StSt Bearings, 10 Speed, 32 Hole, 12 X 142mm
Front Hub	Alloy, Double Sealed, Cartridge Bearing Hub 15mm, 32 Hole
Spokes	DT Champion 2.0mm Black Stainless with Brass Nipples
Rims	Whyte Trail 21 Offset Disc Rims, 32 Hole
Tyre	Maxxis Ardent, 27.5" X 2.25" 60TPI Folding Front, Maxxis Ardent Race, 27.5" X 2.2" 60TPI Folding Rear
Shift Levers	Shimano Deore, 10 Speed, I-Spec
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano SLX, Shadow Plus, 10 Speed
Cassette	Shimano HG-81 SLX, 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Race Face Ride, 36-22, 10 Speed, Compact Double
Bottom Bracket	Race Face
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom Alloy, Low Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S/M, 70mm L, 80mm XL
Grips	Whyte Custom Lock-on
Front Brakes	Shimano BR-615, 180mm Rotor
Rear Brakes	Shimano BR-615, 160mm Rotor
Brake Levers	Shimano BL-615, I-Spec

The award winning 905 is back and better than ever for 2015, with great components, such as the Rockshox Revelation RL fork, and a stunning new paintjob.

The 905 gains the "Get A Grip" seat post clamp system in 2015, providing quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

MBR awarded the 2014 905 the perfect 10/10 in their January group test. "Whyte really has built the perfect 650b trail hardtail" "This bike is simply amazing".

Dropout Code	DROPWH14
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73	599	305	777
M	66.5	73	618	305	805
L	66.5	73	635	305	832
XL	66.5	73	654	305	861
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1119	425	30.9	110	406
M	1139	425	30.9	120	455
L	1169	425	30.9	140	491
XL	1189	430	30.9	150	533

909

TYPICAL USAGE: TRAIL
SRP £2,299



Colour	Matt Granite
Sizes Available	S, M, L
Weight	11.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube and Whyte's adjustable dropout system, Internal Stealth Reverb routing
Fork	RockShox Pike 27.5", RC, 130mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle
Headset	FSA No. 57E Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Hope EVO II with StSt Bearings, XD Driver, 11 Speed, 32 Hole, 12 X 142mm
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	WTB STI 23 TCS 27.5" Tubeless ready rims, 32 Hole
Tyre	WTB Trail Boss TCS 27.5" x 2.25", 60TPI Dual Compound, Folding Front, WTB Beeline TCS 27.5" x 2.2", 60TPI Dual Compound, Folding Rear
Shift Levers	SRAM X1, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X1, 11 Speed, Alloy
Cassette	SRAM XG-1180, 10-42, 11 Speed
Chain	SRAM PCX1, 11 Speed
Crankset	SRAM X1-1200, GXP, 32T, 11 Speed, Alloy
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Fi'zi:k Gobi XM, Mag Rails
Bar	Whyte Custom Alloy, Low Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S/M, 70mm L
Grips	Whyte Custom Lock-on
Front Brakes	Shimano XT, 180mm Rotor
Rear Brakes	Shimano XT, 160mm Rotor
Brake Levers	Shimano XT I-Spec

Our top-end trail hardtail is dripping with lust-worthy components such as SRAM's X-1 11spd drivetrain and an impressive Rockshox Pike RC fork. Combine that with Whyte's geometry and you have an ultra capable bike.

For 2015 the 909 gets full-on Enduro attitude with the multi award winning Pike up front, giving amazing steering precision and poise. If you don't want the complexity of a Full Suspension bike, the 909 gives you maybe the most progressive Trail Hardtail ever made.

Mud clearance and all weather features have long been associated with our designs and when Whyte set out to design this frame there was no exception. We have fitted our unique adjustable dropouts, so you can run the chainstays short in the summer and longer in the winter for more mud clearance or singlespeed if that's your thing.

Dropout Code	DROPW19 Drive Side, DROPW19N Disk Side, DROPW19S Singlespeed
--------------	--

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.2 - 66.8	72.7 - 73.3	599	305	785
M	66.2 - 66.8	72.7 - 73.3	618	305	801
L	66.2 - 66.8	72.7 - 73.3	635	305	830
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1109 - 1129	415 - 435	30.9	110	406
M	1129 - 1149	415 - 435	30.9	120	455
L	1149 - 1169	415 - 435	30.9	140	491

T-129 S

TYPICAL USAGE: TRAIL/XC

SRP £2,199



Colour	Matt Apple/Dark Grey
Sizes Available	S, M, L, XL
Weight	13.5Kg
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube, Intergrip seat clamp and alloy rear Triangle with Maxle 142 dropouts
Fork	RockShox Reba 29", RL, 120mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle Lite
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub 12mm X 142mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB STi19 29" Rims with TCS System, Tubeless Ready, 32 Hole
Tyre	WTB Trail Boss, TCS Light Fast Rolling, 29" X 2.25", Folding Front, WTB Nineline, TCS Light Fast Rolling, 29" X 2.0", Folding Rear
Shift Levers	SRAM X-9 MMX Matchmaker, 10 Speed, Green
Front Derailleur	SRAM X-5, High Direct Mount, 10 Speed
Rear Derailleur	SRAM X-9, Type 2, 10 Speed, Green
Cassette	SRAM PG-1030 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM S1400 GXP, 36-22 29er Trail Ratio, Compact Double, 10 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	RockShox Reverb 125mm Stealth, MMX Matchmaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S, 70mm M, 80mm L/XL
Grips	Whyte Lock-on
Front Brakes	Avid DB5, 180mm Rotor, Internal Routing
Rear Brakes	Avid DB5, 160mm Rotor, Internal Routing
Brake Levers	Avid DB5 MMX Matchmaker

The entry point to the T-129 range features a Rockshox Reverb Stealth seatpost, so you can hit the descent without stopping to drop your saddle out the way.

Awarded the "Trail Bike of the Year" title by What MTB and Bike Radar in 2014, the latest version has an all-new and improved chassis with internal routing, but exactly the same trail-taming authority.

Our Quad 4 suspension layout allows us to apply our contemporary 29er geometry to the 120mm suspension Trail bike category. Short chainstays give this bike the agility of a 27.5" wheel bike but with the inertia and terrain flattening advantages of a larger 29er wheel.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 19mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.3	576	343	808
M	68	74	596	343	813
L	68	73.8	610	343	818
XL	68	73.5	625	343	823

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1125	431	30.9	100	406
M	1145	431	30.9	100	445
L	1160	431	30.9	110	483
XL	1175	431	30.9	120	521

T-129 WORKS

TYPICAL USAGE: TRAIL/XC

SRP £2,699



Colour	Matt Zinc/Burnt Orange
Sizes Available	S, M, L, XL
Weight	13.2Kg
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and InterGrip seat clamp, alloy rear Triangle with 12mm E-Thru 142 dropouts
Fork	Fox Float 32 Performance 29" with CTD FIT, 120mm Travel, Tapered steerer and 15QR
Rear Shock	Float Performance with Boost Valve, Rebound Adjustment and CTD Adjust
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Hope EVO II with StSt Bearings, 10 Speed, 32 Hole, 12 X 142mm
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm Through Axle, 32 Hole
Spokes	DT Champion 2.0mm, Black Stainless Steel Spokes, Brass Nipples
Rims	WTB STi19 29" Rims with TCS System, Tubeless Ready
Tyre	WTB Trail Boss, TCS Light Fast Rolling, 29" X 2.25", Folding Front, WTB Nineline, TCS Light Fast Rolling, 29" X 2.0", Folding Rear
Shift Levers	Shimano XT, I-Spec, 10 Speed
Front Derailleur	Shimano SLX, High Direct Mount, 10 Speed
Rear Derailleur	Shimano XT Shadow Plus, 10 Speed, Black
Cassette	Shimano HG81 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Shimano XT, 38-24 29er Ratio, Compact Double, 10 Speed, Black
Bottom Bracket	Shimano Hollow Tech II
Seatpost	RockShox Reverb 125mm Stealth, 30.9 X 380mm
Seat	Fi'zi:k Gobi XM, Mag Rails
Bar	Whyte Custom Alloy, 15mm Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S, 70mm M, 80mm L/XL
Grips	Whyte Lock-on
Front Brakes	Shimano XT, 180mm Rotor, Internal Routing
Rear Brakes	Shimano XT, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT I-Spec

The Works version of the T-129 is hungry for big rides in big terrain, a true adventure machine with a Shimano 2x10spd drivetrain and Fox shocks.

The 2015 T129 frame has new tubing to increase the torsional stiffness, internal brake routing and Whyte's all new "InterGrip" integrated seat post clamp system.

Speed and flow is the name of the game with the T129 range. Keep off the brakes as long as you dare, tip the bike in as hard as you can and try and work out how you have tamed your favourite single track so fast.

Dropout Code	DROPWHQ4SH
Shock Stroke and Sag Setting	63mm, Sag 19mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.3	576	343	808
M	68	74	596	343	813
L	68	73.8	610	343	818
XL	68	73.5	625	343	823

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1125	431	30.9	100	406
M	1145	431	30.9	100	445
L	1160	431	30.9	110	483
XL	1175	431	30.9	120	521

T-129 WORKS SCR

TYPICAL USAGE: TRAIL/XC

SRP £3,099



Colour	Matt Apple/Black & Teal
Sizes Available	M, L, XL
Weight	13Kg
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip seat clamp, alloy symmetrical SCS rear Triangle
Fork	RockShox Pike 29", RC, 120mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle
Rear Shock	Fox Float Factory Kashima Coating with Boost Valve, Rebound Adjustment and CTD Adjust
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	SRAM Roam 40, 12 x 142mm
Front Hub	SRAM Roam 40, 15 x 100mm
Spokes	SRAM Roam 40, StSt Butted
Rims	SRAM Roam 40, 21mm wide 29", Full UST Rims
Tyre	Maxxis High-Roller II TR 29 X 2.3" EXO Sidewall protection, Folding Front, Maxxis Crossmark TR 29 X 2.1" EXO Sidewall protection, Folding Rear
Shift Levers	SRAM X-1, MMX Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X-1, 11 Speed Alloy
Cassette	SRAM XG-1180 10-42, 11 Speed
Chain	SRAM PCX1, 11 Speed
Crankset	SRAM X1-1400 GXP, 32, 11 Speed Alloy
Bottom Bracket	SRAM GXP Team 73mm
Seatpost	RockShox Reverb 125 Stealth, MMX MatchMaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 750mm Wide
Stem	Whyte Gravity Stem, 40mm M, L, XL
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RS, 4 Pots, 180mm Rotor, Internal Routing
Rear Brakes	SRAM Guide RS, 4 Pots, 160mm Rotor, Internal Routing
Brake Levers	SRAM Guide RS, MMX Matchmaker

Our SCR bikes feature a modified frame with stiffer, symmetrical chainstays and a full-width main pivot. SRAM's 1x11 X-1 drivetrain helps make that happen.

With a wish list spec, the new T129 SCR is the ultimate trail version of our multi award winning T-129 line.

Featuring Whyte's all new "InterGrip" integrated seat post clamping system. SRAM Roam 40 Wheels with 21mm wide welded UST Tubeless rims, combined with Maxxis TR tyres give exceptional levels of control.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16-19mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	68	74	617	335	805
L	68	73.8	637	335	810
XL	68	73.5	657	335	815
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1165	431	30.9	100	445
L	1185	431	30.9	110	483
XL	1205	431	30.9	120	521

529

TYPICAL USAGE: CROSS COUNTRY/TRAIL
SRP £799



Colour	Matt Granite/Orange
Sizes Available	S, M, L
Weight	12.8Kg
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts
Fork	RockShox XC-30, 100mm Travel, Adjustable Rebound, Turn Key Lockout
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-20 29" sleeve joint Offset rims, 32 Hole
Tyre	Maxxis IKON 60TPI, 29"x 2.2", Folding
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Alivio, 9 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-300, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M4000, 40-30-22, 9 Speed, Octalink
Bottom Bracket	Shimano BB-ES25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 180mm rotor, Internal Routing
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	VP Composite with Alloy Cage and Toe Clip

This great value 29er has exceptional geometry, a lightweight frame and a range of UK-proof features, giving the rider the confidence to ride further, faster, more often.

The same high quality frameset features on all the X-29 bikes. For 2015 there's a new frame featuring a chainstay mounted disc mount and internal disc brake routing.

The X-29 geometry is based on the ground breaking 29-C frame. The unique Whyte combination of XC speed, trail bike handling and all-day comfort bring something very special to the 29er movement.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73	600	305	805
M	68.5	73	615	305	820
L	68.5	73	629	305	832
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1113	440	30.9	110	432
M	1128	440	30.9	115	470
L	1143	440	30.9	120	521

629

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £999



Colour	Matt Zinc/Lime & Apple
Sizes Available	S, M, L
Weight	12.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts
Fork	RockShox XC-30 TK 29", Solo Air, 100mm Travel, Alloy Tapered Steerer and Lock out and rebound
Headset	FSA No. 10 upper and 1.5" lower external cup Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-229 29" sleeve joint Offset Rims, 32 Hole Rear, 28 Hole Front
Tyre	Maxxis IKON 60TPI, 29"x 2.2", Folding
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed
Rear Derailleur	SRAM X-7, Type 2, Medium Cage, 10 Speed
Cassette	SRAM PG-1030, 11-36, 10 Speed
Chain	SRAM PC 1031, 10 Speed
Crankset	SRAM S1000 GXP, 36-22 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Gemini, 180mm Rotor, Internal Routing
Rear Brakes	Tektro Gemini, 160mm Rotor, Internal Routing
Brake Levers	Tektro Gemini
Pedals	VP Full Alloy with Toe Clip

Featuring a 2x10 SRAM drivetrain and a lightweight Rockshox fork, the 629 is equally at home lining up at the start of a cross-country race as it is spending long days exploring the hills.

The X-29 geometry is based on the ground breaking 29-C frame. The unique Whyte combination of XC speed, trail bike handling and all-day comfort bring some thing very special to the 29er movement.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73	600	305	805
M	68.5	73	615	305	820
L	68.5	73	629	305	832
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1113	440	30.9	110	432
M	1128	440	30.9	115	470
L	1143	440	30.9	120	521

729

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £1,499



Colour	Matt Granite/Apple
Sizes Available	S, M, L
Weight	11.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts
Fork	RockShox Reba RL 100mm Travel, Fast Black, Alloy Tapered Steerer, 15mm Maxle, Rebound and Compression adjust
Headset	FSA No. 10 upper and 1.5" lower external cup with Cartridge Bearings
Rear Hub	Alloy, Double Sealed, Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed, Cartridge Bearing Hub, 28 Hole, 15mm
Spokes	DT Swiss 2.0mm, Competition Black Stainless Steel
Rims	Whyte XC-229 29" sleeve joint Offset Rims, 32 Hole Rear, 28 Hole Front
Tyre	Maxxis IKON, 120TPI, 29" X 2.2" Folding, Silkworm Puncture Protection
Shift Levers	SRAM X-9 MMX Matchmaker, 10 Speed, Custom Green
Front Derailleur	SRAM X-7, 10 Speed
Rear Derailleur	SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green
Cassette	SRAM PG-1050, 11-36, 10 Speed
Chain	SRAM PC 1031, 10 Speed
Crankset	SRAM S1400 GXP, 36-22 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Custom Lock-on
Front Brakes	Avid DB 5 Matchmaker, 180mm Rotor, Internal Routing
Rear Brakes	Avid DB 5 Matchmaker, 160mm Rotor, Internal Routing
Brake Levers	Avid DB 5 MMX Matchmaker

This great value hardtail is a race-ready weapon that begs to go fast uphill, downhill and everywhere in between. And with such a great parts selection, you've got no excuses.

The same high quality frameset features on all the X-29 bikes. For 2015 there's a new frame featuring a chainstay mounted disk mount and internal disc brake routing.

The X-29 geometry is based on the ground breaking 29-C frame. The unique Whyte combination of XC speed, trail bike handling and all-day comfort bring something very special to the 29er movement.

Dropout Code	DROPWHRC
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73	600	305	805
M	68.5	73	615	305	820
L	68.5	73	629	305	832
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1113	440	30.9	110	432
M	1128	440	30.9	115	470
L	1143	440	30.9	120	521

801

TYPICAL USAGE: CROSS COUNTRY/Trail

SRP £750



Colour	Matt Granite/Lime
Sizes Available	S, M, L, XL
Weight	13.2Kg
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts
Fork	RockShox XC-30 Silver, 100mm Travel, Adjustable Rebound, Tapered Alloy Steerer, Turn Key Lockout
Headset	FSA No. 10 upper and 1.5" lower external cup Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-22, sleeve joint, Offset rims, 32 Hole
Tyre	Maxxis IKON Wire 27.5" x 2.2"
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-200, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M391, 44-32-22, 9 Speed, Octalink
Bottom Bracket	Shimano BB-ES25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	VP Composite with Alloy Cage and Toe Clip

Our range of 650b aluminium hardtails offer a fine balance of fun and speed, and the 801 is the perfect entry point with 27 Shimano gears and upgrade-worthy chassis.

For 2015 there is a brand new high quality X-8 frameset featuring a chainstay disc mount and internal cable and hose routing. Offset rims give equal spoke tension to reduce the asymmetric load on the wheel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, internal routing for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWHRC
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	594	304	779
M	68.5	73.5	608	304	797
L	68.5	73	628	304	822
XL	68.5	73	639	304	851
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107	435	30.9	115	406
M	1123	435	30.9	125	444
L	1137	435	30.9	135	483
XL	1149	435	30.9	145	533

805

TYPICAL USAGE: CROSS COUNTRY/Trail
SRP £999



Colour	Matt Apple/Grey
Sizes Available	S, M, L, XL
Weight	12.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts
Fork	RockShox XC-30 Gold, 100mm Travel, Adjustable Rebound, Tapered Alloy Steerer, Turn Key Lockout
Headset	FSA No. 10 upper and 1.5" lower external cup Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-22, sleeve joint, Offset rims, 32 Hole
Tyre	Maxxis IKON, Wire 27.5" x 2.2"
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed
Rear Derailleur	SRAM X-7, Long Cage, Type 2, 10 Speed
Cassette	SRAM PG-1020 11-36, 10 Speed
Chain	SRAM PC 1031, 10 Speed
Crankset	SRAM FC800, 44-33-22 with Power Spline, 10 Speed
Bottom Bracket	SRAM Power Spline
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Gemini, 160mm Rotor, Internal Routing
Rear Brakes	Tektro Gemini, 160mm Rotor, Internal Routing
Brake Levers	Tektro Gemini
Pedals	VP Composite with Alloy Cage and Toe Clip

Internal cable routing keeps cables clean and clear of grime, whatever the conditions, while Whyte's surefooted geometry will make you want to ride come rain or shine.

Our trail-honed geometry is both fast and reassuring, encouraging you to push your limits on the descents as well as the climbs.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, internal routing and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	594	304	779
M	68.5	73.5	608	304	797
L	68.5	73	628	304	822
XL	68.5	73	639	304	851
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107	435	30.9	115	406
M	1123	435	30.9	125	444
L	1137	435	30.9	135	483
XL	1149	435	30.9	145	533

802 COMPACT

TYPICAL USAGE: CROSS COUNTRY/Trail

SRP £750



Colour	Matt Zinc/Violet & Aqua
Sizes Available	XS, S, M
Weight	13.2Kg
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts
Fork	RockShox XC-30 Silver, 100mm Travel, Solo Air, Adjustable Rebound, Alloy Steerer, Turn Key Lockout
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-22, sleeve joint, Offset rims, 32 Hole
Tyre	Maxxis IKON Wire 27.5" x 2.2"
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-200, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M391, 44-32-22, Silver, 9 Speed with 170mm Cranks, Octalink
Bottom Bracket	Shimano BB-ES25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Sports
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 60mm XS, 60mm S, 70mm M
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga WDS Compact
Pedals	VP Composite with Alloy Cage and Toe Clip

The 802 is available in the XS size, and all sizes sport more compact geometry than the 801 or 805. That means slightly less length for more comfortable reach suiting riders with shorter proportions.

For 2015 there is a brand new high quality X-8 frameset featuring a chainstay disc mount and internal cable and hose routing. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, internal routing for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74	571	304	776
S	68.5	73.5	586	304	784
M	68.5	73.5	600	304	804
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1089	435	30.9	107	381
S	1099	435	30.9	115	406
M	1114	435	30.9	125	444

806 COMPACT

TYPICAL USAGE: CROSS COUNTRY/Trail

SRP £999



Colour	Matt Granite/Aqua
Sizes Available	XS, S, M
Weight	12.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts
Fork	RockShox XC-30 Silver, 100mm Travel, Solo Air, Adjustable Rebound, Tapered Alloy Steerer, Turn Key Lockout
Headset	FSA No. 10 upper and 1.5" lower external cup Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	WTB STi19 27.5" Rims with TCS System, Tubeless Ready, 28 Hole Front, 32 Hole Rear
Tyre	WTB BeeLine TCS Light Fast Rolling, 27.5" x 2.2" Folding Bead
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano Deore RD-M610 Shadow
Cassette	Shimano HG-50, 11-36, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano M523 Hollow Tech, 40-30-22, Silver, 10 Speed with 170mm Cranks
Bottom Bracket	Shimano BB-ES25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's fit
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 60mm XS, 60mm S, 70mm M
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga WDS
Pedals	VP Composite with Alloy Cage and Toe Clip

With compact geometry and shorter 170mm cranks as standard, the 806 allows shorter riders to get all the benefits of the intermediate 650b wheel size.

For 2015 there is a brand new high quality X-8 frameset featuring a chainstay disc mount and internal cable and hose routing. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

The 806 is also tubeless ready - so need to worry about punctures.

Dropout Code	DROPHRC
--------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74	571	304	776
S	68.5	73.5	586	304	784
M	68.5	73.5	600	304	804
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1089	435	30.9	107	381
S	1099	435	30.9	115	406
M	1114	435	30.9	125	444

603

TYPICAL USAGE: CROSS COUNTRY

SRP £525



Colour	Matt Apple/Black & Teal
Sizes Available	S, M, L, XL
Weight	13.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Internal Cable routing, Post Mount Dropouts
Fork	SR XCM, 100mm Travel, Fixed Rebound Damping, Hydro Lockout
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX19, 32 Hole
Tyre	WTB Nano Wire 27.5" x 2.1"
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano Altus, 8 Speed
Rear Derailleur	Shimano Acera RD-M390
Cassette	Shimano HG-41, 11-34, 8 Speed
Chain	Shimano HG-40, 8 Speed
Crankset	Shimano M361, 42-32-22, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S & M, 80mm L & 90mm XL
Grips	Whyte Custom
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	VP Composite with Alloy Cage and Toe Clip

You'll find it hard to believe the 603 is Whyte's entry level mountain bike: with carefully chosen, branded parts and a well designed frame it has all the hallmarks of Whyte's award winning DNA.

The X-6 series is an all new 650b/27.5" range for Whyte. Based on last year's popular X8 frameset it features Whyte's award winning geometry as found on all our XC hardtails. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Code	DROPWH6
-------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	594	304	779
M	68.5	73.5	608	304	797
L	68.5	73	628	304	822
XL	68.5	73	639	304	851
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107	435	30.9	115	406
M	1123	435	30.9	125	444
L	1137	435	30.9	135	483
XL	1149	435	30.9	145	533

604 COMPACT

TYPICAL USAGE: CROSS COUNTRY

SRP £525



Colour	Matt Aqua/Black & White
Sizes Available	XS, S, M
Weight	13.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Dropouts
Fork	SR XCM, 100mm Travel, Fixed Rebound, Hydro Lockout
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-19, 32 Hole
Tyre	WTB Nano Wire 27.5" x 2.1"
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano Altus, 8 Speed
Rear Derailleur	Shimano Acera RD-M390
Cassette	Shimano HG-41, 11-34, 8 Speed
Chain	Shimano HG-40
Crankset	Shimano M361, 42-32-22, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm XS & S, 80mm M
Grips	Whyte Custom
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	VP Composite with Alloy Cage and Toe Clip

Our Compact MTBs feature shorter geometry and components to better fit a smaller rider. The 604 may be our entry level model, but with carefully chosen parts and an exceptional frame it remains distinctly Whyte.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

The X-6 series is an all new 650b/27.5" range for Whyte. Based on last year's popular X8 frameset it features Whyte's award winning geometry as found on all our XC hardtails. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

Dropout Code	DROPWH6
--------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74	571	304	776
S	68.5	73.5	586	304	784
M	68.5	73.5	600	304	804
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1089	435	30.9	107	381
S	1099	435	30.9	115	406
M	1114	435	30.9	125	444

605

TYPICAL USAGE: CROSS COUNTRY

SRP £650



Colour	Matt Zinc/Apple/Black
Sizes Available	S, M, L, XL
Weight	13.4Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Internal Routing, Post Mount Dropouts
Fork	SR XCR, 100mm Travel, Alloy Steerer, Adjustable Rebound, Hydro Lockout
Headset	FSA No. 10 Sealed Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-19, 32 Hole
Tyre	WTB Nano Wire 27.5" x 2.1"
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Alivo RD-M4000 Shadow, 9 Speed
Cassette	Shimano HG-200-9, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M391, 44-32-22, 9 Speed
Bottom Bracket	Shimano BB-UN26 Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 80mm M & L, 90mm XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	VP Composite with Alloy Cage and Toe Clip

Carrying over many of the features and much of the spec of the successful 2014 Whyte 801, the 605 is a bike we're hugely excited to add to our lineup - simply an exceptional MTB.

The X-6 series is an all new 650b/27.5" range for Whyte. Based on last year's popular X8 frameset it features Whyte's award winning geometry as found on all our XC hardtails. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWH6
--------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	594	304	779
M	68.5	73.5	608	304	797
L	68.5	73	628	304	822
XL	68.5	73	639	304	851

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107	435	30.9	115	406
M	1123	435	30.9	125	444
L	1137	435	30.9	135	483
XL	1149	435	30.9	145	533

401

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £899



Colour	Matt Zinc/Emerald/Apple Green
Sizes Available	13"
Weight	10.9Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted
Fork	SR Raidon, 100mm Travel, Alloy Stanchions, Alloy Steerer, Adjustable Rebound, Hydro Lockout
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-401, 28 Hole
Tyre	Continental Race-King Folding 26" x 2.2"
Shift Levers	SRAM X0 GripShift, 10 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X-7, Type 2, 10 Speed, Green
Cassette	SRAM 1020, 11-36, 10 Speed
Chain	SRAM PC1031, 10 Speed
Crankset	SRAM Firex GXP, T33 Single With Chain Guard, 170mm Crank, 10 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Kids
Bar	Whyte Flat Kids Bar, 31.8mm, 580mm Wide
Stem	Whyte Custom, 70mm -6 Deg
Grips	SRAM Lock-On's
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor
Brake Levers	Tektro Auriga WDS, Adjustable Reach
Pedals	VP Composite Kids

We've broken themold with the 401. By putting 26" wheels on a kids MTB we've given a boost in performance similar to an adult switching to a 29er. More confidence, more control and easier riding.

By going the 1 x route and XO grip shift with the spec we've provided an intuitive and easy to use system that is easily operated by smaller hands.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWH9
--------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	68.5	74	563	305	714
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1076	425	30.9	100	331

M-109 CS

TYPICAL USAGE: CROSS COUNTRY/MARATHON

SRP £2,999



Colour	Matt UD Carbon/Orange
Sizes Available	M, L
Weight	12.2Kg
Frame	High-Modulus UD Carbon Front Triangle with Tapered Head Tube, alloy rear Triangle with E-Thru dropouts
Fork	Fox Float 32 Performance 29" with CTD Adjust, FIT, 100mm Travel, Tapered steerer and 15QR
Rear Shock	Fox Float Performance with Boost Valve, Rebound Adjustment and CTD Adjust
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Whyte XC-209-Carbon Wheelset, 32 StSt spokes, 12mm E Thru, Alloy Freehub, 6 Bolt hub with double sealed cartridge bearings
Front Hub	Whyte XC-209-Carbon Wheelset, 28 StSt flat spokes, QR15, 6 Bolt hub with double sealed cartridge bearings
Spokes	Black Stainless Steel Spokes, Alloy Nipples
Rims	Whyte X-C-209-Carbon Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyre	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	Shimano XT I-Spec, 10 Speed
Front Derailleur	Shimano XT, High Direct Mount, 10 Speed
Rear Derailleur	Shimano XT, Shadow Plus, 10 Speed
Cassette	Shimano HG81-10 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Shimano XT, Hollow Tech II, 38-24, 10 Speed
Bottom Bracket	Shimano Hollow Tech II
Seatpost	Whyte Custom 2014 Alloy, 30.9mm x 350mm, 2 bolt clamp
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom 6061 Alloy, Flat, 31.8mm, 730mm Wide
Stem	Whyte Custom, -6 Degree, 80mm M, 90mm L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano XT, 180mm
Rear Brakes	Shimano XT, 160mm
Brake Levers	Shimano XT I-Spec

With a carbon frame and carbon wheels, the M-109 CS is all about minimising weight without compromising stiffness. The result is an endurance rider's dream.

The M-109-CS is a new addition to the line, giving a benchmark Shimano XT spec combined with Whyte's XC-209 carbon wheelset and the carbon mainframe, for a great cross country package.

The carbon front triangle reduces weight, as does the all-new XC-209 carbon wheelset. These carbon wheels from Whyte use wide, low-profile 23mm tubeless-ready carbon rims with Maxxis IKON TR tyres.

Dropout Code	DROPWHQ4SH
Shock Stroke and Sag Setting	50mm, Sag 13-15mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	190mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	69.5	74	599	335	797
L	69.5	73.8	614	335	807

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1125	432	30.9	105	445
L	1140	432	30.9	115	483

M-109 C TEAM

TYPICAL USAGE: CROSS COUNTRY/MARATHON

SRP £4,599



Colour	Matt UD Carbon/Lime
Sizes Available	M, L
Weight	11.5Kg
Frame	High-Modulus UD Carbon Front Triangle with Tapered Head Tube, alloy rear Triangle with E-Thru dropouts
Fork	Fox Float 32 Factory 29" with CTD Adjust, FIT, 100mm Travel, Tapered steerer and 15QR
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Shock	Fox Float Factory with Boost Valve, Rebound Adjustment and CTD Adjust
Rear Hub	Whyte XC-209-Carbon Team Carbon Wheelset, 28 Straight Pull StSt spokes, 12mm E Thru, Alloy Freehub, 6 Bolt hub with double sealed cartridge bearings
Front Hub	Whyte XC-209-Carbon Team Wheelset, 28 Straight Pull StSt flat spokes, QR15, 6 Bolt hub with double sealed cartridge bearings
Spokes	Black Stainless Steel Spokes, DT Swiss Prolock Alloy Nipples
Rims	Whyte X-C-209-C Team Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyre	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	Shimano XTR I-Spec, 11 Speed
Front Derailleur	Shimano XTR, High Direct Mount, 11 Speed
Rear Derailleur	Shimano XTR, Shadow Plus, 11 Speed
Cassette	Shimano XTR1-10 11-40, 11 Speed
Chain	Shimano HG600, 11 Speed
Crankset	Shimano XTR, Hollow Tech II, 36-26, 11 Speed
Bottom Bracket	Shimano Hollow Tech II
Seatpost	Easton EC-70 Matt Carbon, 30.9mm x 400mm, Zero Offset, 2 Bolt Clamp
Seat	Custom Prologo Nago Evo X8, Ti Rail
Bar	Easton EC-70 Matt Carbon Bar, 720mm Wide
Stem	Whyte Custom, -6 Degree, 80mm M, 90mm L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano XTR, 180mm Ice Tech Rotor with metal pads and Cooling Fin's
Rear Brakes	Shimano XTR, 160mm Ice Tech Rotor with metal pads and Cooling Fin's
Brake Levers	Shimano XTR I-Spec

Boasting the latest incarnation of Shimano's legendary XTR groupset, the M-109 C Team comes as standard with the best of everything, from forks and brakes, to wheels and gears.

Designed for long, high-speed days in the saddle. Our Quad 4 suspension delivers efficiency and reliability, built around full complement pivot bearings for smooth operation.

The carbon front triangle reduces weight, as does the XC-209 carbon Team wheelset. These carbon wheels from Whyte use wide, low-profile 23mm tubeless-ready carbon rims.

Dropout Code	DROPWHQ4SH
Shock Stroke and Sag Setting	50mm, Sag 13-15mm
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	190mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	69.5	74	599	335	797
L	69.5	73.8	614	335	807
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1125	432	30.9	105	445
L	1140	432	30.9	115	483

29-C

TYPICAL USAGE: CROSS COUNTRY/RACE

SRP £1,999



Colour	Matt UD Carbon/Apple
Sizes Available	S, M, L
Weight	10.5Kg
Frame	Uni-directional Multi Monocone with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	RockShox Reba RL 100mm Travel, Fast Black coating, Alloy Tapered Steerer, 15mm Maxle Lite, Rebound and Compression adjust
Headset	FSA No. 42E Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte XC-209 Wheelset, 32 StSt spokes, 6 Bolt hub with double sealed cartridge bearings
Front Hub	Whyte XC-209 Wheelset, 28 StSt spokes, 6 Bolt hub, double sealed cartridge bearing, 15mm
Spokes	Black Stainless Steel
Rims	Whyte XC-209, 29" welded joint
Tyre	Maxxis IKON, 60TPI Folding Bead, 29" x 2.2"
Shift Levers	Shimano Deore I-Spec, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed, High Direct Mount
Rear Derailleur	Shimano SLX Shadow Plus, 10 Speed
Cassette	Shimano CS-HG 81, 11-36, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	FSA Comet, PressFit30, 38/24, 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	FSA PressFit 30
Seatpost	Whyte Custom 2014 Alloy, 30.9mm x 400mm, 2 bolt clamp
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom 6061 Alloy, Flat, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano M610, 180mm Rotor
Rear Brakes	Shimano M610, 160mm Rotor
Brake Levers	Shimano M610, I-Spec

The 29-C is as fast as it looks, with an upgrade-worthy carbon fibre frame, confidence inspiring geometry and an enviable parts package.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Lightweight wheels are essential to 29er performance. Whyte's XC-209 welded rim wheelset with 15mm front hub is an upgrade over last years model.

Dropout Code	DROPWH20
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612	304	789
M	69.3	72.8	627	304	809
L	69.3	72.8	641	304	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117	438	30.9	100	431
M	1128	438	30.9	110	470
L	1145	438	30.9	120	521

29-CS

TYPICAL USAGE: CROSS COUNTRY/RACE

SRP £2,999



Colour	Matt UD Carbon/Aqua
Sizes Available	S, M, L
Weight	9.9Kg
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	Fox Float Performance 32, 29" with CTD Adjust, FIT, 100mm Travel, Tapered steerer and 15QR
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte XC-209-Carbon Wheelset, 32 StSt spokes, 6 Bolt hub with double sealed cartridge bearings, Shimano XT QR
Front Hub	Whyte XC-209-Carbon Wheelset, 28 StSt spokes, 6 Bolt hub with double sealed cartridge bearings, 15mm
Spokes	Black Stainless Steel
Rims	Whyte X-C-209-Carbon Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyre	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	Shimano XT I Spec, 10 Speed
Front Derailleur	Shimano SLX, 10 Speed, High Direct Mount
Rear Derailleur	Shimano XTR M986, Shadow Plus, 10 Speed
Cassette	Shimano SLX CS-HG81, 11-36, 10 Speed
Chain	Shimano, HG75, 10 Speed
Crankset	Shimano XT, 38-24 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	Hollow Tech II with FSA PF to BSA Converter
Seatpost	FSA SL-K Matt UD Carbon, 30.9mm x 400mm, 2 bolt clamp
Seat	Whyte Custom dual density, triple panel design
Bar	FSA SL-K Matt UD Carbon, Flat Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M & L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano XT, 180mm Rotor
Rear Brakes	Shimano XT, 160mm Rotor
Brake Levers	Shimano XT I Spec

The upgrade to a carbon fibre wheelset doesn't just save weight at the most important spot, it also boosts stiffness, keeping you glued to the right line, no matter how tough the conditions.

This bike will not only get you round your favourite XC loop in record time, it will also give you the control and balance of the very best of our Whyte trail bikes.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Dropout Code	DROPWH20
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612	304	789
M	69.3	72.8	627	304	809
L	69.3	72.8	641	304	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117	438	30.9	100	431
M	1128	438	30.9	110	470
L	1145	438	30.9	120	521

29-C TEAM

TYPICAL USAGE: CROSS COUNTRY/RACE

SRP £4,999



Colour	Matt UD Carbon/Orange
Sizes Available	S, M, L
Weight	9.5Kg
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	RockShox RS1 29", 100mm Travel, Fast Black coating, Full Carbon uppers and Tapered steerer, 15mm Maxle Lite
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte XC-209-Carbon Team Wheelset, 32 StSt spokes, SRAM X-0 32 Hole, XD Driver for 11 Speed
Front Hub	Whyte XC-209-C Carbon Team Wheelset, 28 StSt spokes, SRAM X-0 28 Hole
Spokes	Double Butted Black Stainless Steel
Rims	Whyte X-C-209-Carbon Team Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyre	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	SRAM XX1 MMX Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XX1, 11Speed
Cassette	SRAM XX1 XG1199 10-42, 11 Speed
Chain	SRAM PCXX1, 11 Speed
Crankset	SRAM XX1, 32T, 11 Speed
Bottom Bracket	Pressfit 30
Seatpost	Easton EC-70 Matt UD Carbon, 30.9mm x 400mm, 2 bolt clamp
Seat	Prologo Custom X-Zero, Ti Rail
Bar	Easton EC-70 Matt UD Carbon, Flat Bar, 31.8mm, 720mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M & L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	SRAM Guide RSC, 170mm Rotor, StSt hardware
Rear Brakes	SRAM Guide RSC, 160mm Rotor, StSt hardware
Brake Levers	SRAM Guide RSC, MMX Matchmaker

Picture your dream cross-country race bike: it looks just like the 29-C Team, right? With the best of everything, including Rockshox' new RS1 inverted fork, this is the bike dreams are made of.

Our unique Whyte frame geometry is more surefooted than a typical light-weight XC race bike, inspiring confidence on more technical sections.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Dropout Code	DROPWH20
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612	304	789
M	69.3	72.8	627	304	809
L	69.3	72.8	641	304	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117	438	30.9	100	431
M	1128	438	30.9	110	470
L	1145	438	30.9	120	521

SAXON CROSS

TYPICAL USAGE: CYCLOCROSS/ALL TERRAIN

SRP £1,499



Colour	Matt Granite/Aqua & Lime
Sizes Available	52cm, 54cm, 56cm, 58cm
Weight	9.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted and Chainstay Post Mount Disk mount
Fork	Straight Bladed Full Carbon Front Fork with Tapered Alloy Steerer with Post Mount Full Carbon Dropouts
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 32 Hole
Front Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	WTB Custom Frequency Team i19 TCS, Tubeless Ready, I-Beam technology, Disk Specific, 32 Hole
Tyre	WTB Cross Wolf, TCS CX Tyre, DNA Compound, 700 x 33c, Black
Shift Levers	SRAM SB700, Full Hydraulic, 10 Speed
Front Derailleur	SRAM Apex, 10 Speed
Rear Derailleur	SRAM X-9, Long Cage, Type 2, 10 Speed
Cassette	SRAM PG-1030, 11-36, 10 Speed
Chain	FSA Team Issue
Crankset	FSA Gossamer Pro Cross EVO-386, 36-46, 10 Speed, Compact Double
Bottom Bracket	EVO-8681
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	FSA Omega Compact
Stem	Whyte -6 Deg, 70mm 52mm, 80mm 54, 90mm 56mm & 58mm
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	SRAM SB700 Hydraulic, 160mm Rotor
Rear Brakes	SRAM SB700 Hydraulic, 160mm Rotor
Brake Levers	SRAM SB700 Hydraulic

The Saxon Cross takes everything we've learnt from MTBs and puts that knowledge into a great value cyclocross package. With hydraulic discs, groundbreaking geometry and select MTB components, this bike is born for the mud.

We have applied our unique Whyte frame geometry to the Saxon Cross, creating Whyte's most versatile all-terrain bike. It's equally at home riding your favourite bridle path, winter training or even commuting. Alternatively, try a CX race this winter - this bike can do it all!

A straight bladed carbon fork with a tapered steerer tube and full carbon dropouts give this bike great front end stiffness and steering precision.

Dropout Code	DROPWHRC
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52cm	70	74	560	280	800
54cm	70	73.5	575	280	814
56cm	70	73	589	280	830
58cm	70	73	598	280	845

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52cm	1050	430	27.2	145	520
54cm	1060	430	27.2	160	540
56cm	1075	435	27.2	175	560
58cm	1085	435	27.2	190	580

SAXON CROSS TEAM

TYPICAL USAGE: CYCLOCROSS/ALL TERRAIN

SRP £2,499



Colour	Matt Granite/Aqua & Lime
Sizes Available	54cm, 56cm
Weight	8.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted and Chainstay Post Mount Disk mount
Fork	Easton EC-90 Straight Bladed Full Carbon Front Fork with Tapered Carbon Steerer, with Post Mount Dropouts
Headset	FSA Integrated Road, No42, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Easton EA90XD, UST Wheelset, XD Driver 11 Speed
Front Hub	Easton EA90XD, UST Wheelset
Spokes	Easton Stainless Steel
Rims	Easton EA90XD, UST Rims
Tyre	Maxxis Mud Wrestler TR, 700 x 33c, 60TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	SRAM Force CX1 11 Speed, Hydraulic Levers
Front Derailleur	N/A
Rear Derailleur	SRAM Force CX1, Mid Cage, 11 Speed
Cassette	SRAM PG-1170, 11-32, 11 Speed
Chain	SRAM PCX1
Crankset	SRAM Force CX, 38T, 170mm Crank Length
Bottom Bracket	GXP
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	FSA Gossamer Wing Compact, 440mm Wide
Stem	Whyte -6 Deg, 80mm 54, 90mm 56
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	SRAM Force CX1, 160mm Rotor
Rear Brakes	SRAM Force CX1, 160mm Rotor
Brake Levers	SRAM Force CX1

A truly groundbreaking cross bike with MTB-inspired geometry, tubeless wheels, hydraulic disc brakes and SRAM's innovative Force CX groupset, this bike is ready for anything.

Whyte geometry makes this bike exceptionally competent and controllable off-road. "1 by 11" technology offers simplicity and efficiency that cannot be rivalled. Full hydraulic disc brakes add stopping power and control.

Easton's straight bladed EC-90 XD carbon fork with its tapered steerer tube gives this bike great front end stiffness and steering precision.

Dropout Code	DROPWHRC
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
54cm	70	73.5	575	280	814
56cm	70	73	589	280	830

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
54cm	1060	430	27.2	160	540
56cm	1075	435	27.2	175	560

STRAWBERRY HILL LADIES

TYPICAL USAGE:

SRP £599



Colour	Granite/Ox Blood
Sizes Available	S, M, L
Weight	12.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Whyte Alloy, curved blade with Alloy Steerer
Headset	FSA No.10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Silver Stainless with Brass Nipples
Rims	Whyte Double Walled Alloy, 700c, 32 Hole
Tyre	Maxxis Roamer, 700 x 42c High Air Volume, with Kevlar Puncture Guard
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Acera, 9 Speed
Cassette	Shimano HG-30, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M391 Acera, 48-36-26
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Selle Royal, Milo Women's fit Saddle
Bar	Whyte Swept Bar, 25.4mm, 600mm Wide, 45mm Sweep
Stem	Whyte Custom, High Rise, 20 Deg
Grips	GP1 Ergon, Swept Bar specific
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro V Brake Levers with Integrated Bell
Pedals	VP Alloy Body with Non Slip Grip

Whyte's take on a stylish, comfortable, lifestyle bike. Combining the elegance of a vintage machine with a 30 speed drivetrain and a remarkably lightweight frame, we've made it even easier to get up the hills, or just to lift up the stairs when you get home.

Comfort was given top priority with the Strawberry Hill. The Selle Royal Milo saddle is highly cushioned but also lightweight. The grips are specifically designed to fit your palm on a swept handle bar bike and even the brake levers have a Kraton insert to add a tactile and comfortable feel.

Full mudguards, a chainset cover and internal cable routing keep all the moving parts away from the rider.

Dropout Code	DROPWHLC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	537	288	663
M	69	74	563	288	686
L	69	73.5	587	288	677
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1066	445	30.9	130	432
M	1080	445	30.9	160	457
L	1100	445	30.9	180	495

FAIRFIELD LADIES

TYPICAL USAGE: ALL TERRAIN

SRP £499



Colour	Matt Granite/Silver
Sizes Available	S, M, L
Weight	11.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with concealed rear brake posts
Fork	6061 Alloy, curved blade with Alloy Steerer and eyelets
Headset	FSA No.10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Silver Stainless with Brass Nipples
Rims	WTB DX-17 700c, 32 Hole
Tyre	Maxxis Roamer 700 x 42c with Kevlar Puncture Protection
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano FD-M191, 8 Speed
Rear Derailleur	Shimano Acera, 8 Speed
Cassette	Shimano CS-HG-31, 11-32, 8 Speed
Chain	Shimano HG-40, 8 Speed
Crankset	Shimano M311, 48-38-28, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro Ergo Style brake lever with Intergrated Bell
Pedals	VP Alloy Body with Non Slip Grip

The Fairfield is where Whyte's ideas of 29" wheel MTB design dove-tails with classic European-style trekking bikes. With a lightweight, comfortable chassis and a full Shimano drivetrain, it will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases standover height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHLC
Recommended Mudguards	WHYMG52

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547	288	712
M	69	74.0	563	288	735
L	69	73.5	587	288	761
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1066	445	30.9	130	432
M	1080	445	30.9	160	457
L	1100	445	30.9	180	495

RIDGEWAY LADIES

TYPICAL USAGE: ALL TERRAIN

SRP £599



Colour	Matt Zinc/Ox Blood
Sizes Available	S, M, L
Weight	13.7Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NEX HLO, 63mm travel with Hydro Lockout
Headset	FSA No.10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Alivio, 9 Speed
Cassette	Shimano CS-HG-200-9, 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M371, 48-36-26, 9 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design With Snake Skin effect
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Vela, 160mm Rotor
Rear Brakes	Tektro Vela, 160mm Rotor
Brake Levers	Tektro Vela, 160mm Rotor
Pedals	VP Composite with Toe Clip

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable women's specific chassis and full Shimano drivetrain will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases standover height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres give extra reliability and piece of mind.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	557	288	728
M	69	74	584	288	747
L	69	73.5	609	288	767
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1083	435	30.9	107	432
M	1095	435	30.9	115	457
L	1105	435	30.9	125	495

MALVERN LADIES

TYPICAL USAGE: All Terrain

SRP £699



Colour	Matt Granite/Cool Grey
Sizes Available	S, M, L
Weight	13.2Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO Lite, 63mm travel, Coil Spring, Hydro Lockout and Alloy Steerer tube
Headset	FSA No.10 Caged Bearings
Rear Hub	Shimano FH-RM-33, 32 Hole with Centre-Lock
Front Hub	Shimano HB-RM-33, 32 Hole with Centre-Lock
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Deore, 9 Speed
Cassette	Shimano HG-300-9, 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M391 Acera, 48-36-26, Octalink, 9 Speed
Bottom Bracket	Shimano ES-25, Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, triple panel design With Snake Skin effect
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano BR-M355, 160mm Rotor
Rear Brakes	Shimano BR-M355, 160mm Rotor
Brake Levers	Shimano BR-M355
Pedals	VP Composite with Toe Clip

To save yet more weight, the Malvern's suspension fork comes with an alloy steerer tube, which is significantly lighter than steel. Combined with a lightweight, comfortable chassis and full Shimano drivetrain, the Malvern Ladies will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifts working smoother for longer.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases standover height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	557	288	728
M	69	74	584	288	747
L	69	73.5	609	288	767
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1083	435	30.9	107	432
M	1095	435	30.9	115	457
L	1105	435	30.9	125	495

CALEDONIAN LADIES

TYPICAL USAGE: ALL TERRAIN

SRP £850



Colour	Matt Bone/Cool Grey
Sizes Available	S, M, L
Weight	13Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO Lite, 63mm travel, Coil Spring, Hydro Lockout and Alloy steerer tube
Headset	FSA No.10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano LX T670, 10 Speed
Cassette	Shimano CS-HG-62, 11-34, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano TS21, 48-36-26, Octalink Hollow Tech, 10 Speed
Bottom Bracket	Shimano ES-25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design With Snake Skin effect
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M447, 160mm Rotor
Rear Brakes	Shimano M447, 160mm Rotor
Brake Levers	Shimano M445
Pedals	VP Composite with Alloy Cage and Toe Clip

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure - are you?

All the same key design features as the Unisex version, with the added benefit of a partially dropped top tube. This increases standover height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control).

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	557	288	728
M	69	74.0	584	288	747
L	69	73.5	609	288	767
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1083	435	30.9	107	432
M	1095	435	30.9	115	457
L	1105	435	30.9	125	495

RIDGEWAY

TYPICAL USAGE: ALL TERRAIN

SRP £599



Colour	Matt Granite/Cool Grey
Sizes Available	S, M, L
Weight	13.8Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NEX HLO, 63mm travel, Hydro Lockout
Headset	FSA No.10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Alivio, 9 Speed
Cassette	Shimano HG-200-9, 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M371, 48-36-26, 9 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Vela, 160mm Rotor
Rear Brakes	Tektro Vela, 160mm Rotor
Brake Levers	Tektro Vela
Pedals	VP Composite with Toe Clip

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable chassis and full Shimano drivetrain will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain. Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	589	288	784
M	69	73.5	614	288	815
L	69	73	629	288	842
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1101	435	30.9	115	457
M	1121	435	30.9	125	495
L	1131	435	30.9	135	546

FAIRFIELD

TYPICAL USAGE: ALL TERRAIN

SRP £499



Colour	Matt Granite/Cool Grey
Sizes Available	S, M, L
Weight	11.8Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted, concealed rear brake post
Fork	6061 Alloy, curved blade with Alloy Steerer and Eyelets
Headset	FSA No.10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Silver Stainless with Brass Nipples
Rims	WTB DX-17 700c, 32 Hole
Tyre	Maxxis Roamer 700 x 42c with Kevlar Puncture Protection
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano FD-M191, 8 Speed
Rear Derailleur	Shimano Acraea, 8 Speed
Cassette	Shimano HG-31, 11-32, 8 Speed
Chain	Shimano HG-40, 8 Speed
Crankset	Shimano M311, 48-38-28, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro Ergo Style brake lever with Intergrated Bell
Pedals	VP Alloy Body with Non Slip Grip

The Fairfield is where Whyte's ideas of 29" wheel MTB design dove-tails with classic European-style trekking bikes. With a lightweight, comfortable chassis, and a full Shimano drivetrain, it will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame. Our bikes are also mud guard ready for all year use.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain. Full Shimano drivetrain to give years of unrivalled performance and puncture resistant tyres for extra reliability and piece of mind.

Dropout Code	DROPWHLC
Recommended Mudguards	WHYMG52

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	563	288	773
M	69	73.5	587	288	798
L	69	73.5	605	288	838
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1080	445	30.9	160	457
M	1100	445	30.9	180	495
L	1120	445	30.9	200	546

MALVERN

TYPICAL USAGE: ALL TERRAIN

SRP £699



Colour	Matt Granite/Cool Grey
Sizes Available	S, M, L, XL
Weight	13.3Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO, 63mm travel, Coil Spring, Hydro Lockout and Alloy Steerer tube
Headset	FSA No.10 Caged Bearings
Rear Hub	Shimano FH-RM-33, 32 Hole with Centre-Lock
Front Hub	Shimano HB-RM-33, 32 Hole with Centre-Lock
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Deore, 9 Speed
Cassette	Shimano HG-300-9, 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M391 Acera, 48-36-26, Octolink, 9 Speed
Bottom Bracket	Shimano ES-25, Octolink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano BR-M355, 160mm Rotor
Rear Brakes	Shimano BR-M355, 160mm Rotor
Brake Levers	Shimano BL-M335
Pedals	VP Composite with Toe Clip

To save yet more weight, the Malvern's suspension fork comes with an alloy steerer tube, which is significantly lighter than steel. Combined with a lightweight, comfortable chassis and full Shimano drivetrain, the Malvern will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	589	288	784
M	69	73.5	614	288	815
L	69	73	629	288	842
XL	69	73	644	288	864
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1101	435	30.9	115	457
M	1121	435	30.9	125	495
L	1131	435	30.9	135	546
XL	1146	435	30.9	145	585

CALEDONIAN

TYPICAL USAGE: ALL TERRAIN

SRP £850



Colour	Matt Zinc/Aqua
Sizes Available	S, M, L
Weight	13Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO, 63mm travel, Coil Spring, Hydro Lockout and Alloy Steerer tube
Headset	FSA No.10 Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano LX, 10 Speed
Cassette	Shimano Deore HG-62, 11-34, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano T521, 48-36-26, Octalink, Hollow Tech, 10 Speed
Bottom Bracket	Shimano ES-25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M447, 160mm Rotor
Rear Brakes	Shimano M447, 160mm Rotor
Brake Levers	Shimano M445
Pedals	VP Composite with Alloy Cage and Toe Clip

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure - are you?

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	589	288	784
M	69	73.5	614	288	815
L	69	73	629	288	842
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1101	435	30.9	115	457
M	1121	435	30.9	125	495
L	1131	435	30.9	135	546

WHITECHAPEL

TYPICAL USAGE: URBAN/COMMUTER

SRP £550



Colour	Matt Zinc
Sizes Available	S, M, L, XL
Weight	10.4Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork, Post mount with Single Eyelets
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Lower bearing, Double Sealed upper bearing
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Shining A-240, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tyre	Vittoria Zaffiro, 700 x 28c, Black, with Puncture Protection
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Acera, 9 Speed
Cassette	Shimano HG-200-9, 11-32 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Lasco 42T, with chain Guard
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 60mm S & M, 70mm L & XL
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced Composite Platform

The Whitechapel is all about simplicity: a single chain ring and nine gears at the back will give years of urban use, and by placing the disc brake caliper inside the rear triangle, adding mudguards or a rack couldn't be easier.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

Our shaped, butted and uniquely profiled rear stays give all our fast urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	568	275	725
M	70	73.5	596	275	757
L	70	73	613	275	789
XL	70	73	627	275	820
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	145	406
M	1069	420	27.2	165	445
L	1084	420	27.2	185	495
XL	1099	420	27.2	205	533

CARNABY WOMEN'S

TYPICAL USAGE: URBAN/COMMUTER

SRP £550



Colour	Matt Bone
Sizes Available	S, M, L
Weight	10.4Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork, Post Mount with Single Eyelets
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Lower bearing, Double Sealed upper bearing
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Shining A240 Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tyre	Vittoria Zaffiro, 700 x 28c, Black, with Puncture Protection
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Acera, 9 Speed
Cassette	Shimano HG-200-9, 11-32 9 Speed
Chain	KMC X9, 9 Speed
Crankset	Lasco 39T, with Alloy Chain Guard
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 60mm S & M, 70mm L
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tekro Auriga 160mm Rotor
Rear Brakes	Tekro Auriga 160mm Rotor
Brake Levers	Tekro Auriga WDS
Pedals	Fibre reinforced Composite Platform

The Carnaby is all about simplicity, with the addition of female-specific components such as Whyte's women's specific saddle. Nine gears operated by one shifter will give years of urban use while disc brakes guarantee consistent stopping performance whatever the weather.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle for easy fitment of a rack or mudguards.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547	272	738
M	69.5	73.5	572	272	741
L	70	73	598	272	773
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040	420	27.2	140	394
M	1052	420	27.2	160	432
L	1069	420	27.2	180	470

SHOREDITCH

TYPICAL USAGE: URBAN/COMMUTER

SRP £650



Colour	Matt Granite/Grey
Sizes Available	S, M, L, XL
Weight	10.2Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork, with Post Mount and Single Eyelets
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Lower bearing, Caged Double Sealed upper bearing
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Shining A-240, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tyre	Vittoria Zaffrio, 700 x 28c, Black, with Puncture Protection
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore Shadow Plus, 10 Speed
Cassette	Shimano HG-50-10, 11-36 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Lasco 42T Alloy Chain ring and Guard, 10 Speed
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 60mm S & M, 70mm L & XL
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced Composite Platform

The Shoreditch employs mountain biking clutch mech technology to ensure the chain stays put no matter how rough the route becomes. Elsewhere, the upgrade to a carbon fork saves weight and smooths out road chatter.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout mounts the hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required. 1 by 10 MTB gearing promises years of reliable urban use and hydro discs guarantee consistent performance in all conditions.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	568	275	725
M	70	73.5	596	275	757
L	70	73	613	275	789
XL	70	73	627	275	820
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	145	406
M	1069	420	27.2	165	445
L	1084	420	27.2	185	495
XL	1099	420	27.2	205	533

VICTORIA WOMEN'S

TYPICAL USAGE: URBAN/COMMUTER

SRP £699



Colour	Matt Granite/Aqua
Sizes Available	S, M, L
Weight	10.2Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork, Post mount Dropout with Single Eyelets
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Folding Black/Aqua, with Puncture Protection
Shift Levers	Shimano Sora SL-3500, 9 Speed
Front Derailleur	Shimano Sora FD-R3500, 9 Speed
Rear Derailleur	Shimano Sora RD-3500, 9 Speed
Cassette	Shimano HG-300, 11-32 9 Speed
Chain	Shimano HG-53, 9 Sped
Crankset	FSA Tempo 50-34, 9 Speed, Compact, 170mm Crank arm length
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 70mm XS & S, 80mm M
Grips	Whyte double Density, Lock-on
Front Brakes	Tektro Auriga WDS, Light weight 160mm Rotor
Rear Brakes	Tektro Auriga WDS, Light weight 160mm Rotor
Brake Levers	Tektro Auriga WDS
Pedals	Composite with Alloy Cage and Toe Clip

A lightweight aluminium frame employs compact geometry to make this bike perfect for shorter riders who want a wide-ratio 2x9spd Shimano drivetrain.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Our shaped, butted and uniquely profiled rear stays give all our fast urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547	272	738
M	69.5	73.5	572	272	741
L	70	73	598	272	773
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040	420	27.2	140	394
M	1052	420	27.2	160	432
L	1069	420	27.2	180	470

PORTOBELLO

TYPICAL USAGE: URBAN/COMMUTER

SRP £750



Colour	Matt Granite/Apple
Sizes Available	S, M, L, XL, XXL
Weight	10.3Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Black, with Puncture Protection
Shift Levers	Shimano Sora SL-3500, 9 Speed
Front Derailleur	Shimano Sora FD-3500, 9 Speed
Rear Derailleur	Shimano Sora RD-3500, 9 Speed
Cassette	Shimano HG-300, 11-32 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	FSA Tempo 50-34, 9 Speed, Compact
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on's
Front Brakes	Tektro Auriga, Light weight 160mm Rotor
Rear Brakes	Tektro Auriga, Light weight 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced Composite with Toe Clip

Our lightweight aluminium frame uses MTB-inspired geometry to increase confidence on rough city streets while a carbon fork does a great job of damping out road buzz.

The Portobello gains an all new carbon fork for 2015, with full carbon dropouts and an eyelet for mud guards.

Our shaped, butted and uniquely profiled rear stays give all our Fast Urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	568	272	722
M	70	73.5	596	272	754
L	70	73	613	272	786
XL	70	73	627	272	817
XXL	70	72.5	642	272	846
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	145	406
M	1069	420	27.2	165	445
L	1084	420	27.2	185	495
XL	1099	420	27.2	205	533
XXL	1114	425	27.2	225	584.2

PIMLICO WOMEN'S

TYPICAL USAGE: URBAN/COMMUTER

SRP £850



Colour	Matt Plum/Grey
Sizes Available	S, M, L
Weight	10Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Gaurds
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Folding Black/Grey, with Puncture Protection
Shift Levers	SRAM Via Centro, 10 Speed
Front Derailleur	SRAM Via Centro, 10 Speed
Rear Derailleur	SRAM Via Centro, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via Centro, 48-32, 10 Speed, Compact
Bottom Bracket	SRAM Power Spline, 68mm Shell
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm XS & S, 80mm M
Grips	Whyte double Density, Lock-on
Front Brakes	Tektro Auriga WDS, Light weight 160mm Rotor
Rear Brakes	Tektro Auriga WDS, Light weight 160mm Rotor
Brake Levers	Tektro Auriga WDS
Pedals	Fibre reinforced Composite with Toe Clip

A lightweight aluminium frame employs compact geometry to make this bike a perfect fit for female riders, while a carbon fork does a great job of damping out road buzz.

Based on our high performance mountain bike geometry, the Pimlico has a long wheelbase and relaxed head angle for high speed stability, a shorter stem for excellent slow speed manoeuvrability and slightly shorter and lower top tube to fit a woman's physique better.

The Pimlico takes advantage of SRAM's Via Centro groupset, specifically designed for urban riding with optimised ratios and slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547	272	738
M	69.5	73.5	572	272	741
L	70	73	598	272	773
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040	420	27.2	140	394
M	1052	420	27.2	160	432
L	1069	420	27.2	180	470

CAMBRIDGE

TYPICAL USAGE: URBAN/COMMUTER

SRP £850



Colour	Matt Zinc/Aqua
Sizes Available	S, M, L, XL
Weight	10.1Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection
Shift Levers	SRAM Via Centro, 10 Speed
Front Derailleur	SRAM Via Centro, 10 Speed
Rear Derailleur	SRAM Via Centro, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via Centro, 48-32, 10 Speed, Compact
Bottom Bracket	SRAM Power Spline, 68mm Shell
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on's
Front Brakes	Tektro Gemini, 160mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor
Brake Levers	Tektro Gemini
Pedals	Fibre reinforced Composite with Toe Clip

We were excited to be able to spec SRAM's Via Centro urban groupset on the Cambridge. With a 2x10 drivetrain, it will help you conquer even the hilliest of cities.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required. Via Centro group has a slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	568	272	722
M	70	73.5	596	272	754
L	70	73	613	272	786
XL	70	73	627	272	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	145	406
M	1069	420	27.2	165	445
L	1084	420	27.2	185	495
XL	1099	420	27.2	205	533

STIRLING

TYPICAL USAGE: URBAN/COMMUTER
SRP £999



Colour	Matt Granite/Burnt Orange
Sizes Available	S, M, L, XL, XXL
Weight	9.8Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Gaurds
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	DT Champion, 2.0mm Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection
Shift Levers	SRAM Via GT, 10 Speed
Front Derailleur	SRAM Via Centro, 10 Speed
Rear Derailleur	SRAM Via GT, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via GT, 48-32 Urban Compact, 10 Speed
Bottom Bracket	SRAM GXP XR
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	GP1 Ergon, Dual Density
Front Brakes	Tektro Gemini, 160mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor
Brake Levers	Tektro Gemini
Pedals	Fibre reinforced Composite with Toe Clip

The Stirling is our top of the range aluminium urban bike, boasting Tektro's powerful Gemini disc brakes and SRAM's superb Via GT drivetrain.

Based on our high performance mountain bike geometry, the Stirling has a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent low speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	568	272	722
M	70	73.5	596	272	754
L	70	73	613	272	786
XL	70	73	627	272	817
XXL	70	72.5	642	272	846
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	145	406
M	1069	420	27.2	165	445
L	1084	420	27.2	185	495
XL	1099	420	27.2	205	533
XXL	1114	425	27.2	225	584.2

MONTPELLIER

TYPICAL USAGE: URBAN/COMMUTER

SRP £1,499



Colour	Matt UD Black/Dark Grey
Sizes Available	M, L, XL
Weight	9.1Kg
Frame	Full Carbon Monocoque with tapered headtube and internal cable routing and Full Carbon Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Tapered Steerer and Full Carbon Dropouts
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	DT Champion 2.0mm, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection
Shift Levers	SRAM Via GT, MMX Matchmaker, 10 Speed
Front Derailleur	SRAM Via GT 10 Speed
Rear Derailleur	SRAM Via GT 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via GT, 48-32 Urban Compact, 10 Speed
Bottom Bracket	SRAM GXP 73mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, Riser Bar 30mm, 580mm Wide
Stem	Whyte, 80mm M, 90mm L & XL
Grips	GP1 Ergon Grip, Dual Density
Front Brakes	SRAM DB5, 160mm Rotor
Rear Brakes	SRAM DB5, 160mm Rotor
Brake Levers	SRAM DB5, MMX Matchmaker
Pedals	None

Whyte's latest carbon technology comes to the urban market, with a frame that is 300g lighter than its earlier iteration. SRAM's Via GT groupset completes an impressive package.

We have incorporated our "Oversize/Undersize" approach from our carbon hardtails to give great power delivery away from the lights, but with class leading comfort. For 2015 we have added full carbon dropouts helping this year's impressive weight saving.

Based on our high performance mountain bike geometry, the Montpellier bridges the gap between out-right road speed and MTB control, with its long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

Dropout Code	DROPWHRD
Recommended Mudguards	N/A

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70	73.5	597	272	744
L	70	73	616	272	776
XL	70	73	623	272	804
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1069	420	27.2	140	445
L	1084	420	27.2	160	495
XL	1099	420	27.2	180	533

SOMERSET WOMEN'S

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £799



Colour	Matt Granite/Lime & Aqua
Sizes Available	47cm, 49cm, 51cm, 53cm
Weight	10.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Alloy Front Fork, with Eyelets, Post Mount disk mount, Tapered Steerer
Headset	FSA No. 23 Integrated Road, 1 1/2" lower Sealed Cartridge Bearing and 1 1/8" upper Caged Double Sealed
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 28 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection
Shift Levers	Shimano ST-3500 SORA, 9 Speed
Front Derailleur	Shimano FD-3500 SORA, 9 Speed
Rear Derailleur	Shimano RD-3500 SORA, 9 Speed
Cassette	Shimano HG-30, 11-32, 9 Speed
Chain	Shimano HG53, 9 Speed
Crankset	FSA Vero, 34-50, 9 Speed, Compact Double
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg, 800mm 47cm, 90mm 49cm/51cm, 100mm 53cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-3500 SORA with In Line brake levers
Pedals	Fibre reinforced Composite with Toe Clip

The Somerset's compact geometry makes for a more comfortable female-specific fit. Combined with lightweight aluminium tubing and an 18spd Shimano drivetrain you have a bike that loves the hills.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with deep section RD-7 wheels and disc brakes will give years of reliable all-season performance.

Ergonomic Wing handlebar, combined with tuned bar width and stem length make for a comfortable fit. In-line brake levers give more control in traffic.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
47cm	71.5	75	507	269	721
49cm	72	74.5	515	272	743
51cm	72.5	74	525	272	777
53cm	73	73.5	535	272	794
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
47cm	985	425	27.2	115	470
49cm	985	425	27.2	130	490
51cm	985	425	27.2	145	510
53cm	985	425	27.2	160	530

DEVON WOMEN'S

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £999



Colour	Matt Zinc/Violet & Aqua
Sizes Available	47cm, 49cm, 51cm, 53cm
Weight	10.3Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Full Carbon Front Fork, Tapered Alloy Steerer, with Post Mount full carbon Dropouts and eyelet for Mud Gaurds
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection, Folding
Shift Levers	Shimano ST-3500 Sora, 9 Speed
Front Derailleur	Shimano FD-3500 Sora, 9 Speed
Rear Derailleur	Shimano RD-4601 Tiagra
Cassette	Shimano HG-30 Sora 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	FSA Omega 34-50, 9 Speed, 170mm Crank Length, Compact Double
Bottom Bracket	FSA Mega Exo
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg, 800mm 47cm, 90mm 49cm/51cm, 100mm 53cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-4600 with In Line Brake Levers
Pedals	Fibre reinforced Composite with Toe Clip

The Devon's TRP HyRd disc brakes use an innovative hybrid cable/hydraulic system to provide powerful braking whatever the conditions. Compact geometry makes for a more comfortable female-specific fit.

A strong alloy 6061 frame, with mudguard and rack eyelets combined with deep section offset rimmed RD-7 wheels will give years of reliable all-season performance.

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte Road Disc range offers Cyclo Cross durability with Road geometry.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
47cm	71.5	75	507	269	721
49cm	72	74.5	515	272	743
51cm	72.5	74	525	272	777
53cm	73	73.5	535	272	794
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
47cm	985	425	27.2	115	470
49cm	985	425	27.2	130	490
51cm	985	425	27.2	145	510
53cm	985	425	27.2	160	530

SUSSEX

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £799



Colour	Matt Zinc/Lime
Sizes Available	50cm, 52cm, 54cm, 56cm, 58cm
Weight	10.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Alloy Front Fork, with Eyelets, Post Mount disk mount, Tapered Steerer
Headset	FSA No. 42 Integrated Road, 1 1/2" lower Sealed Cartridge Bearing and 1 1/8" upper Sealed Ball Retainer
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection
Shift Levers	Shimano ST-3500 SORA, 9 Speed
Front Derailleur	Shimano FD-3500 SORA, 9 Speed
Rear Derailleur	Shimano RD-3500 SORA, 9 Speed
Cassette	Shimano HG-30, 11-32, 9 Speed
Chain	Shimano HG53, 9 Speed
Crankset	FSA Vero, 34-50, 9 Speed, Compact Double
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-3500 SORA
Pedals	Fibre reinforced Composite with Toe Clip

Our lightweight aluminium frame offers large tyre clearances, great geometry and reliable disc braking, making it a perfect companion for big rides out in the hills.

Whether you're commuting longer distances, winter training or entering summer sports, the Whyte road disc range offers Cyclo Cross levels of durability with pure road speed.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with deep section offset rimmed RD-7 wheels and disc brakes will give years of reliable all-season performance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	72	74.5	525	272	764
52cm	72.5	74	540	272	782
54cm	73	73.5	555	272	799
56cm	73	73	570	272	815
58cm	73	73	585	272	831
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	993	425	27.2	130	500
52cm	998	425	27.2	145	520
54cm	1003	425	27.2	160	540
56cm	1013	425	27.2	175	560
58cm	1028	425	27.2	190	580

DORSET

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £999



Colour	Matt Granite/Apple
Sizes Available	52cm, 54cm, 56cm, 58cm
Weight	10Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Full Carbon Front Fork, Tapered Alloy Steerer, with Post Mount full carbon Dropouts and eyelet for Mud Guards
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection, Folding
Shift Levers	Shimano ST-3500 Sora, 9 Speed
Front Derailleur	Shimano FD-3500 Sora, 9 Speed
Rear Derailleur	Shimano RD-4601 Tiagra
Cassette	Shimano CS-3500 Sora 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	FSA Omega 34-50, 9 Speed, Compact Double
Bottom Bracket	FSA Mega Exo
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-3500
Pedals	Fibre reinforced Composite with Toe Clip

An upgrade to a carbon fork dampens road buzz, while 28mm tyres offer great comfort and incredible traction. TRP HyRd disc brakes provide impressive braking.

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte Road Disc range offers Cyclo Cross durability with pure Road geometry.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with deep section Offset Rimmed RD-7 wheels and TRP Hydro/Mechanical disc brakes will give years of reliable all-season performance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52cm	72.5	74	540	272	782
54cm	73	73.5	555	272	799
56cm	73	73	570	272	815
58cm	73	73	585	272	831

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52cm	998	425	27.2	145	520
54cm	1003	425	27.2	160	540
56cm	1013	425	27.2	175	560
58cm	1028	425	27.2	190	580

SUFFOLK

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £1,199



Colour	Matt Granite/Orange & Aqua
Sizes Available	52cm, 54cm, 56cm, 58cm
Weight	10Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Full Carbon Front Fork, Tapered Alloy Steerer, with Post Mount full carbon Dropouts and eyelet for Mud Guards
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole, 11 Speed
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection, Folding
Shift Levers	Shimano 105 ST-5800, 11 Speed
Front Derailleur	Shimano 105 FD-5800, 11 Speed
Rear Derailleur	Shimano 105 RD-5800, 11 Speed
Cassette	Shimano 105 CS-5800 11-32, 11 Speed
Chain	Shimano CN-600, 11 Speed
Crankset	FSA Gossamer Pro EVO-386 34-50, 11 Speed, Compact Double
Bottom Bracket	FSA EVO-8681
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano 105 ST-5800
Pedals	Full Alloy with Toe Clip

The Suffolk benefits from Shimano's new 11-speed 105 groupset, with a wide-ratio cassette to make getting up the hills a breeze. On the descents, reliable TRP disc brakes will slow you down.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with deep section R-7 wheels and disc brakes will give years of reliable all-season performance.

Best in Test in the Cycling Plus "Bikes For All Seasons" group test. The Suffolk was described as a "Fantastic all-round road bike with superb hydraulic brakes"

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52cm	72.5	74	540	272	782
54cm	73	73.5	555	272	799
56cm	73	73	570	272	815
58cm	73	73	585	272	831
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52cm	998	425	27.2	145	520
54cm	1003	425	27.2	160	540
56cm	1013	425	27.2	175	560
58cm	1028	425	27.2	190	580

CORNWALL

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £1,799



Colour	Matt UD/White & Grey
Sizes Available	51cm, 54cm, 57cm, 60cm
Weight	8.6Kg
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	Straight Bladed Full Carbon Front Fork, Tapered Alloy Steerer, with Post Mount full carbon Dropouts and eyelet for Mud Guards
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 32 Hole
Front Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection, Folding
Shift Levers	SRAM SB700, Full Hydraulic, 10 Speed
Front Derailleur	SRAM Apex with Chain Stopper, 10 Speed
Rear Derailleur	SRAM Rival, 32T Max Capacity, WiFlI Function, 11 Speed
Cassette	SRAM PG-1030, 11-28, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	FSA Gossamer Pro EVO-386 34-50, 10 Speed, Compact Double
Bottom Bracket	FSA EVO-8681
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg, 100mm 51, 110mm 54 & 57, 120mm 60
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	SRAM SB700 Hydraulic, 160mm Rotor
Rear Brakes	SRAM SB700 Hydraulic, 160mm Rotor
Brake Levers	SRAM SB700 Hydraulic
Pedals	None

An upgrade to a full-carbon fibre frame and SRAM's SB700 hydraulic disc brakes makes the Cornwall something of a dream machine. The perfect British road bike? We think so!

Hydraulic discs deliver modulation and control in all weather conditions. However there is more to the Cornwall than just brakes, the ability to fit full length mud guards combined with strong wheels make it the perfect all weather workhorse, with the added comfort and performance only carbon can give.

A carbon bladed fork, 27.2mm seat post and skinny seat stays combine to give a beautifully smooth ride.

Dropout Code	DROPWHRD
Recommended Mudguards	N/A

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51cm	71.5	72.5	543	279	758
54cm	72	72.5	553	279	788
57cm	72	72	568	282	817
60cm	72	72	593	281	843

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51cm	1005	430	27.2	120	510
54cm	1011	430	27.2	155	540
57cm	1022	430	27.2	180	570
60cm	1047	430	27.2	210	600

STOWE RIVAL

TYPICAL USAGE: Road
SRP £1,999



Colour	Matt UD/Aqua
Sizes Available	51cm, 54cm, 57cm
Weight	8.6Kg
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	Straight Bladed Full Carbon Front Fork with Tapered Alloy Steerer and Post Mount full carbon Dropouts
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 28 Hole
Front Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 24 Hole
Spokes	DT Champion 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	Whyte Road Disk 28mm Offset Deep Section, 28 Hole Rear and 24 Front
Tyre	Maxxis Relix, 700 x 25c, 170tpi, with Silkshield Puncture Protection, Folding
Shift Levers	SRAM Rival, Full Hydraulic, 11 Speed
Front Derailleur	SRAM Rival, Yaw function with Chain Stopper, 11 Speed
Rear Derailleur	SRAM Force, 32T Max Capacity, WiFi Function, 11 Speed
Cassette	SRAM PG-1130, 11-28, 11 Speed
Chain	SRAM PC-1130
Crankset	SRAM Rival 50-34 compact, Yaw function, 11 Speed
Bottom Bracket	GXP
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar, 400mm 51, 420mm 54, 440mm 57 & 60
Stem	Whyte -6 Deg (flipflop design), 90mm 51, 100mm 54, 110mm 57 & 60
Grips	Whyte Anti Slip with 3M Reflective logos
Front Brakes	SRAM Rival Hydraulic, 160mm Rotor
Rear Brakes	SRAM Rival Hydraulic, 160mm Rotor
Brake Levers	SRAM Rival Hydraulic

Our new road platform has more aggressive geometry than the RD-7 for better aerodynamics and more speed. An 11-speed SRAM Rival groupset with hydraulic disc brakes helps seal the deal.

SRAM's new group includes a Yaw shifting crankset and WiFi rear derailleur to give the very latest in modern road bike shifting.

Up front we have a carbon bladed fork with internal hose management. A 27.2mm seat post and skinny seat stays offer added compliance for comfort.

Dropout Code	DROPWHRD
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51cm	72.5	73.5	540	272	750
54cm	73	73.5	549	272	784
57cm	73	73	566	274	808
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51cm	999	430	27.2	120	510
54cm	1005	430	27.2	155	540
57cm	1016	430	27.2	180	570

STOWE ULTEGRA

TYPICAL USAGE: Road

SRP £3,199



Colour	Matt UD/Aqua
Sizes Available	51cm, 54cm, 57cm
Weight	7.5Kg
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	Straight Bladed Full Carbon Front Fork with internal hose routing, Tapered Carbon Steerer, with Post Mount full carbon Dropouts
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Road Disk Carbon Wheelset, 28 Straight Pull StSt spokes, Alloy Freehub, Center-Lock hub with double sealed cartridge bearings
Front Hub	Whyte Road Disk Carbon Wheelset, 24 Straight Pull StSt spokes, Center-Lock hub with double sealed cartridge bearings
Spokes	Black Stainless Steel Spokes, DT Swiss Prolock Alloy Nipples
Rims	Whyte Road Disk Carbon, 24mm Deep, 28 Hole Rear and 24 Front
Tyre	Maxxis Relix, 700 x 25c, 170tpi, with Silkshield Puncture Protection, Folding
Shift Levers	Shimano 685, Full Hydraulic, 11 Speed
Front Derailleur	Shimano Ultegra with Chain Stopper, 11 Speed
Rear Derailleur	Shimano Ultegra, Max capacity 32T, 11 Speed
Cassette	SRAM PG-1130, 11-28, 11 Speed
Chain	FSA Team Issue, 11 Speed
Crankset	FSA SL-K, UD Carbon, EVO-386 36-52, Compact Double, 11 Speed
Bottom Bracket	EVO 386
Seatpost	FSA SL-K, UD Carbon, 27.5mm X 350mm Lg, 20mm offset.
Seat	Fi'zi:k Aliante Delta, Maganese Rail
Bar	FSA SL-K Compact, UD Carbon, 400/420/440mm
Stem	Whyte -6 Deg (flipflop design), 90mm 51, 100mm 54, 110mm 57 & 60
Grips	Whyte Anti Slip with 3M Reflective logos
Front Brakes	Shimano 785, Full Hydraulic, 160mm Rotor
Rear Brakes	Shimano 785, Full Hydraulic, 140mm Rotor
Brake Levers	Shimano 685, Full Hydraulic

The Stowe Ultegra is the road bike we've all dreamt of: hydraulic brakes, a lightweight and efficient carbon frame, carbon wheels and an 11-speed drivetrain make this a bona-fide dream machine.

Shimano full hydraulic brakes are the standout spec on this bike giving all year round modulation and control in all weather conditions. However there is more to the Stowe Ultegra than just brakes, a full Shimano Ultegra groupset combined with the clever FSA Gossamer Pro EVO-386 crankset that allows a 30mm alloy axle to fit a BSA external BB shell.

Up front we have a full carbon bladed fork with internal hose management. A 27.2mm seat post and skinny seat stays combine with Whyte's own carbon rimmed low profile wheels to give a beautifully smooth and efficient ride.

Dropout Code	DROPWHRD
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51cm	72.5	73.5	540	272	750
54cm	73	73.5	549	272	784
57cm	73	73	566	274	808

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51cm	999	430	27.2	120	510
54cm	1005	430	27.2	155	540
57cm	1016	430	27.2	180	570